



CMI110



Features

- Mini-ITX system supports iBASE DC-in motherboards (MI920, MB890 & MB500)
- Expandable for various applications
- Available in black color
- One 2.5" HDD drive bay
- Medium box design with 2 x 5cm fan (optional)
- Optional wall mount kit

CMI110 Specifications

System Mainboard	MI920, MB890 & MB500
Construction	SECC
Chassis Color	Black
I/O Connectors	2x Front USB, 1x Front Power On/Off button, Rear side I/O Based on motherboard SPEC
Expansion Slots	1x PCI slot
Storage	1x 2.5" HDD drive bay
Power Supply	60W power adaptor
Mounting	Optional wall mount kit
Dimensions	202mm(W) x 200mm(D) x 111mm(H)

Environmental

Operating Temperature	0°C~60°C (32°F~140°F)
Relative Humidity	5 ~ 90% @ 40°C, (non-condensing)

Ordering Information

CMI110-500C	Chassis for MB500 Mini-ITX, w/ 60W power adaptor, 2.5" HDD holder
CMI110-890C	Chassis for MB890 Mini-ITX, w/ 60W power adaptor, 2.5" HDD holder
CMI110-920C	Chassis for MI920 Mini-ITX, w/ 60W power adaptor, 2.5" HDD holder
MI920EL-C6K	Intel® Celeron® M, 910GME Mini-ITX motherboard w/ VGA, DVI and 10/100
MI920EF	Socket 479 for Pentium® M/Celeron® M, 915GME Mini-ITX motherboard w/ VGA, DVI, Mini PCI-E, LVDS, 10/100 and PCI-E Gigabit LAN
MB890-R	Socket 479 for Pentium® M/Celeron® M, 852GM Mini-ITX motherboard w/ VGA and 10/100 LAN
MB890F-R	Socket 479 for Pentium® M/Celeron® M, 855GME Mini-ITX motherboard w/ VGA, 1394, TV-out and Gigabit LAN
MB500-R	AMD Geode LX700, 433MHz, CS5536 Mini-ITX motherboard w/ VGA and 10/100 LAN
MB500F-R	AMD Geode LX800, 500MHz, CS5536 Mini-ITX motherboard w/ VGA and dual 10/100 LAN,
CMI110-BRKT	Wall mount kit for CMI110



Remarks: 1. ODM/OEM is available
2. Specifications are subject to change without prior notice.

Motherboards

1

Disk-Size SBCs

2

CPU Modules

3

PC/I/O Plus

4

CPU Cards

5

AGP & MicroAGP

6

Embedded Systems

7

Network Security Appliance

8