



## CMI201



### Features

- Mini-ITX system supports IBASE Mini-ITX motherboards except LGA775-based
- With motherboard's I/O shields and extra 2x USB ports
- Available in black color
- LEDs for Standby and Power
- One 2.5" HDD drive bay
- Supports one PCI slot
- Optional 85W DC power supply
- Optional wall mount kit

### CMI201 Specifications

System Mainboard	IBASE Mini-ITX motherboards (except LG775-based)
Construction	SECC
Chassis Color	Black
I/O Connectors	Flexible IBASE Mini-ITX motherboard's I/O shields, 3x COM ports, extra 2x USB port, Standby LED, Power LED, ATX power On/Off/Reset, DC 12V output connectors
Expansion Slots	1x PCI slot
Storage	1x 2.5" HDD drive bay
Power Supply	Output Power: DC 60W or 85W (ATX Power) Input Voltage: 115~230VAC (Nom.)
Mounting	Optional wall mount kit
Dimensions	300mm(W) x 200mm(D) x 72mm(H)

### Environmental

Operating Temperature	0°C~ 45°C (32°F~113°F)
Relative Humidity	5 ~ 90% @ 40°C, (non-condensing)

### Ordering Information

CMI201-60	Chassis for Mini-ITX (low power), w/ 60W PSU, 2.5" HDD holder, 1x PCI-E (optional IP271-R, IP119-R riser & LVDS/DVI ports)
CMI201-85	Chassis for Mini-ITX (low power), w/ 85W PSU, 2.5" HDD holder, 1x PCI-E (optional IP271-R, IP119-R riser & LVDS/DVI ports)
MI910	Socket 478 Intel® Core™2 Duo Mini-ITX motherboard w/ Intel® GME965 chipset
MB899	Socket 478 Intel® Core™2 Duo Mini-ITX motherboard w/ Intel® 945GME chipset
MB899X	Socket 478 Intel® Core™2 Duo Mini-ITX motherboard w/ Intel® 945GME chipset
MB896	Socket 479 Pentium® M/Celeron® M Mini-ITX motherboard w/ Intel® 915GME chipset
MB850	Socket 478 Pentium® 4(M) Mini-ITX M/B w/ Intel® 845GV chipset
MB770	VIA Eden-V4/C7 Mini-ITX motherboard w/ VIA CN700 chipset
IP119	Riser card with 1x PCI-E(x16) (see page 24)
IP271-R	Riser card with 1x PCI (see page24)
CMI201-BRKT	Wall mount kit for CMI201

Remarks: 1. Use only CPU/heatsink with height fitting the chassis-not touching the chassis top cover.  
2. ODM/OEM is available.